


Voltage Controlled Oscillator-VCO CVCO55CL-1188-1212




PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			1188	MHz
Upper Frequency:	1212			MHz
Tuning Voltage:	0		8.0	VDC
Supply Voltage:	11.4	12.0	12.6	VDC
Output Power:	+6.0	+8.0	+10.0	dBm
Supply Current:		20		mA
Harmonic Suppression (2 nd Harmonic):		-20		dBc
Pushing:		1.0	2.0	MHz/V
Pulling, all Phases:		1.0	2.0	MHz pk-pk
Tuning Sensitivity:		15		MHz/V
Phase Noise @ 10kHz offset:		-110		dBc/Hz
Phase Noise @ 100kHz offset:		-133		dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			100	pF
Operating Temperature Range:	-40		+85	$^{\circ}\text{C}$
Storage Temperature Range:	-45		+90	$^{\circ}\text{C}$


Phase Noise
(1 Hz BW, Typical)




Tuning Curve
(Typical)



Voltage Controlled Oscillator-VCO CVCO55CL-1188-1212



TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO55CL-1188-1212	Release Date:	14-Feb-08
Revision Level:	B	Responsible:	C. Vales

Specification is subject to change without notice

Page 2 of 2