



[查询"B81122C1562M"供应商](#)

## Film Capacitors

### EMI Suppression Capacitors (MKP)

**Series/Type:** B81122  
**Date:** August 2004

© EPCOS AG 2004. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

### Typical applications

- Y2 class for interference suppression
- "Line to ground" applications

### Climatic

- Max. operating temperature: 100 °C
- Climatic category (IEC 60068-1):  
40/100/21  $\boxed{e} = 10 \text{ mm}$   
40/085/21  $\boxed{e} \geq 15 \text{ mm}$

### Construction

- Dielectric: polypropylene (MKP)
- Internal series connection (for  $\boxed{e} \geq 15 \text{ mm}$ )
- Plastic case (UL 94 V-0)
- Epoxy resin sealing (UL 94 V-0)

### Features

- Very small dimensions
- Self-healing properties

### Terminals

- Parallel wire leads, lead-free tinned
- Standard lead lengths: 6 – 1 mm
- Special lead lengths available on request

### Marking

Manufacturer's logo, lot number, date code, rated capacitance (coded), cap. tolerance (code letter), rated AC voltage, series number, sub-class (Y2), dielectric code (MKP), climatic category, passive flammability category, approvals.


### Delivery mode

Bulk (untaped)  
Taped (Ammo pack or reel)  
For taping details, refer to chapter "Taping and packing".

### Approvals

| Marks of conformity                                                                 | Standards                 | Certificate                                                                         |
|-------------------------------------------------------------------------------------|---------------------------|-------------------------------------------------------------------------------------|
|  | EN 132400, IEC 60384-14   | 138600 ( $\boxed{e} = 10 \text{ mm}$ )<br>138603 ( $\boxed{e} \geq 15 \text{ mm}$ ) |
|  | UL 1414<br>CSA C22.2 No.1 | E97863<br>E97863                                                                    |

### Dimensional drawing




### Dimensions in mm

| Lead spacing<br>$\boxed{e}$ | Lead diameter $d_1$ |
|-----------------------------|---------------------|
| 10 mm                       | 0.6                 |
| 15 ... 27.5 mm              | 0.8                 |

### Marking example




KMK0824-9



### Overview of available types

| Lead spacing | 10 mm | 15 mm | 22.5 mm | 27.5 mm |
|--------------|-------|-------|---------|---------|
| $C_R$ (μF)   |       |       |         |         |
| 0.0010       |       |       |         |         |
| 0.0015       |       |       |         |         |
| 0.0022       |       |       |         |         |
| 0.0033       |       |       |         |         |
| 0.0047       |       |       |         |         |
| 0.0056       |       |       |         |         |
| 0.0068       |       |       |         |         |
| 0.010        |       |       |         |         |
| 0.015        |       |       |         |         |
| 0.022        |       |       |         |         |
| 0.027        |       |       |         |         |
| 0.033        |       |       |         |         |
| 0.047        |       |       |         |         |
| 0.056        |       |       |         |         |
| 0.068        |       |       |         |         |
| 0.10         |       |       |         |         |
| 0.15         |       |       |         |         |
| 0.22         |       |       |         |         |
| 0.33         |       |       |         |         |



查询"B81122C1562M"供应商

B81122

Y2 / 250 VAC

## Ordering codes and packing units


| Lead spacing<br>mm | C <sub>R</sub><br>μF | Max. dimensions<br>w × h × l<br>mm | Ordering code<br>(composition see<br>below) | Ammo<br>pack<br>pcs./unit | Reel<br>pcs./unit | Untaped<br>pcs./unit |
|--------------------|----------------------|------------------------------------|---------------------------------------------|---------------------------|-------------------|----------------------|
| 10                 | 0.0010               | 4.0 × 9.0 × 13.0                   | B81122C1102M***                             | 1000                      | 1700              | 1000                 |
|                    | 0.0015               | 4.0 × 9.0 × 13.0                   | B81122C1152M***                             | 1000                      | 1700              | 1000                 |
|                    | 0.0022               | 5.0 × 11.0 × 13.0                  | B81122C1222M***                             | 830                       | 1300              | 1000                 |
|                    | 0.0033               | 5.0 × 11.0 × 13.0                  | B81122C1332M***                             | 830                       | 1300              | 1000                 |
|                    | 0.0047               | 6.0 × 12.0 × 13.0                  | B81122C1472M***                             | 680                       | 1100              | 1000                 |
|                    | 0.0056               | 6.0 × 12.0 × 13.0                  | B81122C1562M***                             | 680                       | 1100              | 1000                 |
|                    | 0.0068               | 6.0 × 12.0 × 13.0                  | B81122C1682M***                             | 680                       | 1100              | 1000                 |
| 15                 | 0.010                | 6.0 × 11.0 × 18.0                  | B81122A1103M***                             | 960                       | 1100              | 1000                 |
|                    | 0.015                | 7.0 × 12.5 × 18.0                  | B81122A1153M***                             | 830                       | 900               | 1000                 |
|                    | 0.022                | 8.5 × 14.5 × 18.0                  | B81122A1223M***                             | 680                       | 700               | 500                  |
|                    | 0.027                | 8.5 × 14.5 × 18.0                  | B81122A1273M***                             | 680                       | 700               | 500                  |
|                    | 0.033                | 9.0 × 17.5 × 18.0                  | B81122A1333M***                             | 640                       | 700               | 500                  |
| 22.5               | 0.047                | 7.0 × 16.0 × 26.5                  | B81122A1473M***                             | 580                       | 600               | 630                  |
|                    | 0.056                | 8.5 × 16.5 × 26.5                  | B81122A1563M***                             | 480                       | 500               | 510                  |
|                    | 0.068                | 10.5 × 16.5 × 26.5                 | B81122A1683M***                             | 390                       | 400               | 540                  |
|                    | 0.10                 | 10.5 × 20.5 × 26.5                 | B81122A1104M***                             | 390                       | 400               | 540                  |
| 27.5               | 0.15                 | 11.0 × 21.0 × 31.5                 | B81122A1154M***                             | —                         | 350               | 320                  |
|                    | 0.22                 | 13.5 × 23.0 × 31.5                 | B81122A1224M***                             | —                         | 250               | 260                  |
|                    | 0.33                 | 18.0 × 27.5 × 31.5                 | B81122A1334M***                             | —                         | —                 | 200                  |

Further E series and intermediate capacitance values on request.

## Composition of ordering code


+ = Capacitance tolerance code:  
M = ±20%

\*\*\* = Packaging code:  
289 = Ammo pack  
189 = Reel  
000 = Untaped (lead length 6 – 1 mm)



## Technical data

|                                                                                                                                                                    |                                                                                                |                                          |                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------|
| Max. operating temperature T <sub>op,max</sub>                                                                                                                     | +100 °C                                                                                        |                                          |                         |
| Dissipation factor tan δ (in 10 <sup>-3</sup> )<br>at 20 °C (upper limit values)                                                                                   |                                                                                                | C <sub>R</sub> ≤ 0.1 μF                  | C <sub>R</sub> > 0.1 μF |
|                                                                                                                                                                    | at 1 kHz                                                                                       | 1.0                                      | 1.0                     |
|                                                                                                                                                                    | 100 kHz                                                                                        | 5.0                                      | —                       |
| Insulation resistance R <sub>ins</sub><br>or time constant τ = C <sub>R</sub> · R <sub>ins</sub><br>at 20 °C, rel. humidity ≤ 65%<br>(minimum as-delivered values) | 30 000 MΩ                                                                                      |                                          |                         |
| DC test voltage                                                                                                                                                    | 2700 V, 2 s ( $\varnothing \geq 15$ mm)<br>2500 V, 2 s ( $\varnothing = 10$ mm)                |                                          |                         |
| Passive flammability category<br>to IEC 40 (CO) 752                                                                                                                | C                                                                                              |                                          |                         |
| Maximum continuous AC voltage (V <sub>AC</sub> )                                                                                                                   | 405 V (50/60 Hz) ( $\varnothing \geq 15$ mm)<br>305 V (50/60 Hz) ( $\varnothing = 10$ mm)      |                                          |                         |
| Rated AC voltage (IEC 60384-14)                                                                                                                                    | 250 V (50/60 Hz)                                                                               |                                          |                         |
| Maximum continuous DC voltage (V <sub>DC</sub> )                                                                                                                   | 1000 V ( $\varnothing \geq 15$ mm)<br>1200 V ( $\varnothing = 10$ mm)                          |                                          |                         |
| Operating AC voltage V <sub>op</sub> at high<br>temperature                                                                                                        | T <sub>A</sub> ≤ 100 °C                                                                        | V <sub>op</sub> = V <sub>AC</sub>        | (continuously)          |
|                                                                                                                                                                    | T <sub>A</sub> ≤ 100 °C                                                                        | V <sub>op</sub> = 1.25 · V <sub>AC</sub> | (1000 h)                |
| Damp heat test                                                                                                                                                     | 21 days / 40 °C / 93% relative humidity                                                        |                                          |                         |
| Limit values after damp heat test                                                                                                                                  | Capacitance change  ΔC/C  ≤ 5%                                                                 |                                          |                         |
|                                                                                                                                                                    | Dissipation factor change Δ tan δ ≤ 0.5 · 10 <sup>-3</sup> (at 1 kHz)                          |                                          |                         |
|                                                                                                                                                                    | Insulation resistance R <sub>ins</sub> ≤ 1.0 · 10 <sup>-3</sup> (at 10 kHz)                    |                                          |                         |
|                                                                                                                                                                    | or time constant τ = C <sub>R</sub> · R <sub>ins</sub> ≥ 50% of minimum<br>as-delivered values |                                          |                         |



B81122

Y2 / 250 VAC

[查询"B81122C1562M"供应商](#)

### Pulse handling capability

"dV/dt" represents the maximum permissible voltage change per unit of time for non-sinusoidal voltages, expressed in V/ $\mu$ s.


"k<sub>0</sub>" represents the maximum permissible pulse characteristic of the waveform applied to the capacitor, expressed in V<sup>2</sup>/ $\mu$ s.

*Note:*

*The values of dV/dt and k<sub>0</sub> provided below must not be exceeded in order to avoid damaging the capacitor.*

### dV/dt and k<sub>0</sub> values


| Lead spacing                               | 10 mm   | 15 mm   | 22.5 mm | 27.5 mm |
|--------------------------------------------|---------|---------|---------|---------|
| dV/dt in V/ $\mu$ s                        | 550     | 400     | 200     | 150     |
| k <sub>0</sub> in V <sup>2</sup> / $\mu$ s | 388 000 | 282 000 | 141 000 | 106 000 |



## Impedance Z versus frequency f

(typical values)

Lead spacing = 10 mm



Lead spacing  $\geq 15$  mm

