查询"116737"供应商

ADVANCE®
adhesive tapes

ADVANCE TAPES INTERNATIONAL Ltd
P.O. BOX 122, LEICESTER, U.K. LE4 5RA
Tel: 0116 251 0191 Telex: 34555 ADTAPE G
Fax: 0116 285 3070

Health and Safety Data Sheet

ISO 9002 EFQM HS2

7054993 / 7054981 / 7054970 / 7052678.

WATERPROOF SELF ADHESIVE FABRIC TAPES

AT153, 159, 160, 163, 164, 169, 170, 171, 175, 180, 181, 200

AT560, 563, 566, 712, ROLLATAPE AT271, AT293

DESCRIPTION:

Cloth material coated on one side with polythene and on the other with a pressure-sensitive adhesive, the latter consisting mainly of resins and rubber-like materials. AT153 is interleaved with a crepe paper.

RECOMMENDED GENERAL USES:

Carton Closing, Drum Sealing, Weather Proofing, Jointing, and Protection.

See appropriate Technical Data sheet for individual tapes. Where the product is to be used for any purpose other than that indicated on the Technical Data sheet the use should be referred to the supplier.

Only AT293 *Premier* closure plate tape is recommended for gas fire back plate sealing to British Gas specification PRS10.

APPLICATION:

Ensure that all surfaces to be bonded are dry, free from dust, grease and other contaminants. Surfaces to be bonded, and tape to be applied should also be at a temperature within the limits of the "Application Temperature" recommended in the relevant Technical Data sheet. This is particularly important if the tape has been stored in a cold area. Apply the tape using the maximum amount of pressure possible, smoothing down to achieve 100% contact.

Joins in rolls of tape may occasionally be found. Every endeavour is made to reduce these to a minimum but users should not rely on the tape being one continuous length. When using tapes that have siliconised paper as an interleave, remove this paper from the floor area as quickly as possible to minimise the risk of slipping. Self adhesive tape is not a hazard to health providing it is used correctly.

© Copyright Advance Tapes International Ltd 1995. Issue No.3. B. 216

查询"116737"供应商

SKIN CONTACT:

A good standard of personal hygiene should be maintained. Wash hands with soap and water after use and especially before handling food. The tapes have not been formulated and tested for prolonged skin contact and should not be used as a medical plaster or as a hand protection tape.

People with sensitive skin or those concerned about skin abrasion should take suitable precautions eg. proprietary barrier cream or gloves.

ACCIDENTAL INGESTION/EYE CONTACT:

Seek medical advice urgently.

STORAGE:

Store at the recommended storage temperature and protect from dust, moisture, direct sunlight, corrosive, and solvent fumes. Keep out of the reach of children.

SHELF LIFE:

1 year if stored in accordance with the recommended storage instructions, however for wider rolls (greater than 300mm) and/or under more adverse conditions this period may be reduced. If in doubt contact the supplier.

FIRE RISK:

These tapes are combustible. For small fires use any common extinguishing method. If large quantities are to be stored seek advice from the local Fire Authority about fire-fighting equipment and procedures. This may include the need for air supply breathing apparatus.

DISPOSAL:

As combustible, non-toxic landfill. Because of its combustibility large quantities should be dispersed in small amounts over the landfill site. Incinerate only in purpose-built incinerators.

This information is based on current knowledge and experience. The purpose of this data sheet is to supply information regarding health and safety and it should not be treated as a specification for the products.

Issue Date 4/10/96