


查询"33RH14.2X28.5X6.35"供应商

SPECIFICATION FOR APPROVAL

CUSTOMER : FARNELL				DATE : MAY 17, 1995																																			
PART NO. : 33RH 14.2X28.5X6.35 (559-519)				DWG. NO. : RH-048																																			
(1) MECHANICAL ASSEMBLY 				A	14.2±0.3	m/m																																	
				B	28.5±0.6	m/m																																	
				C	6.35±0.25	m/m																																	
				D		m/m																																	
				E		m/m																																	
				F		m/m																																	
				G		m/m																																	
				H		m/m																																	
				I		m/m																																	
				1ST COLOR		2ND COLOR		3RD COLOR		4TH COLOR																													
(2) ELECTRICAL REQUIREMENTS <table border="1"> <tr> <td>TEST FREQUENCY</td> <td>MHZ</td> <td>L</td> <td>OHM</td> </tr> <tr> <td>TEST FREQUENCY</td> <td>MHZ</td> <td>C</td> <td>PF</td> </tr> <tr> <td></td> <td></td> <td>Q</td> <td></td> </tr> <tr> <td></td> <td></td> <td>SRF</td> <td>MHZ</td> </tr> <tr> <td></td> <td></td> <td>RDC</td> <td>OHM</td> </tr> <tr> <td></td> <td></td> <td>IDC</td> <td>mA</td> </tr> <tr> <td>TEST FREQUENCY</td> <td>25 MHZ</td> <td>Z</td> <td>150⁻⁰ OHM</td> </tr> <tr> <td>TEST FREQUENCY</td> <td>100 MHZ</td> <td>Z</td> <td>220⁻⁰ OHM</td> </tr> </table>				TEST FREQUENCY	MHZ	L	OHM	TEST FREQUENCY	MHZ	C	PF			Q				SRF	MHZ			RDC	OHM			IDC	mA	TEST FREQUENCY	25 MHZ	Z	150 ⁻⁰ OHM	TEST FREQUENCY	100 MHZ	Z	220 ⁻⁰ OHM	(3) SCHEMATIC			
TEST FREQUENCY	MHZ	L	OHM																																				
TEST FREQUENCY	MHZ	C	PF																																				
		Q																																					
		SRF	MHZ																																				
		RDC	OHM																																				
		IDC	mA																																				
TEST FREQUENCY	25 MHZ	Z	150 ⁻⁰ OHM																																				
TEST FREQUENCY	100 MHZ	Z	220 ⁻⁰ OHM																																				
(4) TEST INSTRUMENTS HP 4191A RF IMPEDANCE ANALYZER.																																							
MATERIAL		SPEC.		APPROVED BY																																			
CORE				CHECKED BY  DRAWN BY 																																			
WIRE		0.8φ T.C.W. X 220 m/m																																					
WINDING		1/2 TS.																																					

CUSTOMER : FARNELL					DATE : MAY 17, 1995			
PART NO. : 33RH 14.2X28.5X6.35 (559-519)					DWG. NO. : RH-048			
MEAS. ITEM		Z (OHM)	Z (OHM)	A m/m	B m/m	C m/m	D m/m	E m/m
SPEC	YOUR							
	SUGGEST	150 ⁻⁰	220 ⁻⁰	14.2±0.3	28.5±0.6	6.35±0.25		
TEST FREQ.		25 MHZ	100 MHZ					
1		184	275	14.40	28.60	6.54		
2		186	281	14.39	28.62	6.50		
3		186	278	14.38	28.54	6.54		
4		185	279	14.44	28.59	6.57		
5		184	276	14.45	28.65	6.55		
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
$\bar{X}$		185	278	14.41	28.60	6.54		
R		2	6	0.07	0.11	0.07		
YOUR SAMPLE								
TEST CONDITION: TEMP. 23 °C R.H. 84 %							APPROVED BY 	
							CHECKED BY 	
							DRAWN BY 	