

Heavy Duty Vibration Meter

Measures Acceleration, Velocity and Displacement plus a PC interface
Stores the maximum and minimum values for later recall

Features:

- Ranges — Acceleration: 656ft/s² (200m/s²), Velocity: 7.87in/s (200mm/s), Displacement: 0.078in (2mm)
- Remote vibration sensor with magnetic adapter on 39"(1m) cable
- Wide frequency range of 10Hz to 1kHz
- Resolution to 2ft/s² (0.5m/s²), 0.02in/s (0.5mm/s), and 0.001in (0.005mm)
- Basic accuracy of $\pm(5\% + 2$ digits)
- RMS or Peak Value measurement modes
- Manual/Auto store/recall up to 500 readings
- Optional Windows® 95/98/NT/2000/XP compatible software allows captured readings to be downloaded to your PC for further analysis
- Data Hold freezes the reading in the display
- Auto shut-off saves battery life
- 9V battery power or optional AC adaptor
- Dimensions: 7.1 x 2.8 x 1.3" (180 x 72 x 32mm); Weight with Probe: 0.87lbs (395g)
- Complete with remote sensor, magnetic mount, 9V battery, protective rubber holster with stand, and hard carrying case



Applications:

- Motors, bearings
- Fans
- Pumps
- Rotating machinery
- Plant maintenance

Ordering Information:

407860 Heavy Duty Vibration Meter, Mounted pickup
 407860-NIST 407860 with NIST Certificate
 156119 117V AC Adaptor
 156221 220V AC Adaptor
 407001 Data Acquisition software and cable
 407001-USB USB adaptor for 407001

