





ELECTRICAL SPECIFICATIONS:

1.0 TURNS RATIO: (P3-P2) : (J4-J5)
(P5-P4) : (J6-J3)
(P9-P8) : (J8-J7)
(P10-P11) : (J2-J1)

2.0 INDUCTANCE: (P3-P2) ; (P5-P4)
(P10-P11) ; (P9-P8)

3.0 LEAKAGE INDUCTANCE: P3-P2 (WITH J4 AND J5 SHORT)
P5-P4 (WITH J6 AND J3 SHORT)
P9-P8 (WITH J8 AND J7 SHORT)
P10-P11 (WITH J1 AND J2 SHORT)

4.0 INTERWINDING CAPACITANCE: (P3-P2) : (J4-J5)
(P5-P4) : (J6-J3)
(P9-P8) : (J8-J7)
(P10-P11) : (J2-J1)

5.0 DC RESISTANCE: (J6-J3) ; (J2-J1) ; (J7-J8) : (J4-J5)

: 1 : 1 ±2%
: 1 : 1 ±2%
: 1 : 1 ±2%
: 1 : 1 ±2%

: 350 uH MIN. @ 0.1V, 100KHz, 8 mA DC BIAS
: 350 uH MIN. @ 0.1V, 100KHz, 8 mA DC BIAS

: 0.3uH MAX. @ 1MHz
: 0.3uH MAX. @ 1MHz
: 0.3uH MAX. @ 1MHz
: 0.3uH MAX. @ 1MHz

: 35pf MAX @ 1MHz
: 35pf MAX @ 1MHz
: 35pf MAX @ 1MHz
: 35pf MAX @ 1MHz

: 1.2 ohms Max.

Bel Stewart Connector
11118 Susquehanna Trail, South
Glen Rock, Pa 17327-9199
717.234.7512

MagJack®

<http://www.stewartconnector.com>

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND PROPERTY OF BEL STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONTENT OF BEL STEWART CONNECTOR. THE SUBJECT MATTER MAY BE PATENTED OR A PATENT MAY BE PENDING.

SHEET 1 OF 4

DRAWING NO.

SI-50076-F

REV. 14

[查询"SI-50076-F"供应商](#)

6.0 RETURN LOSS: 1MHz TO 30MHz
30MHz TO 60MHz
60MHz TO 80MHz
80MHz TO 100MHz
: -19dB MIN.
: -13dB MIN.
: -12dB MIN.
: -10dB MIN.

7.0 DIELECTRIC WITHSTAND: (J1,J2) TO (P10,P11) ; (J5,J4) TO (P3-P2)
(J3,J6) TO (P5,P4) ; (J8,J7) TO (P9, P8)
: 1500 VAC
: 1500 VAC

8.0 INSERTION LOSS: RS=RL=100 ohms
100KHz TO 125MHz
: -1.1 dB TYP

9.0 RISE TIME: RS=100 OHMS AND RL = 100 OHMS
OUTPUT VOLTAGE = 1 V peak
PULSE WIDTH= 112nS
: 3.0 nS MAX
: 3.0 nS MAX

10.0 CROSS TALK: 1-100 MHz
: -[33-20 LOG ($\frac{F}{50 \text{ MHz}}$)] MIN.

11.0 COMMON TO COMMON MODE ATTENUATION: 1MHz TO 100MHz
: -35dB TYP

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND PROPERTY OF BEL STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONTENT OF BEL STEWART CONNECTOR. THE SUBJECT MATTER MAY BE PATENTED OR A PATENT MAY BE PENDING.

Bel Stewart Connector
11118 Susquehanna Trail, South
Glen Rock, Pa 17327-9199
717.234.7512









<http://www.stewartconnector.com>

SHEET
2 OF 4

DRAWING NO.
SI-50076-F

REV.
14



NOTES:

- CONNECTOR MATERIALS:
HOUSING: THERMOPLASTIC UL94 V-0
CONTACT/SHIELD: COPPER ALLOY
SHIELD PLATING: NICKEL OR TIN
CONTACT PLATING: SELECTIVE GOLD,
50 MICRO-INCHES MIN. IN CONTACT AREA.
- PIN NOT ELECTRICALLY CONNECTED MAYBE OMITTED.
SEE ELECTRICAL DRAWING FOR OMITTED PINS.
- TOLERANCES COMPLY WITH F.C.C. DIMENSION REQUIREMENTS.
- ALL TOLERANCES NOT OTHERWISE SPECIFIED TO BE ± .005 [0.13]
- REFLOW AND WAVE SOLDER COMPATIBLE -260°C FOR
10 SECONDS MAX.

查询"SI-50076-F"信息

Bel Stewart Connector
11118 Susquehanna Trail, South
Glen Rock, Pa 17327-9199
717.234.7512

MagJack®

<http://www.stewartconnector.com>



THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND PROPERTY OF BEL STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONTENT OF BEL STEWART CONNECTOR. THE SUBJECT MATTER MAY BE PATENTED OR A PATENT MAY BE PENDING.

SHEET 3 OF 4

DRAWING NO.

SI-50076-F

REV. 05



1. THE SUGGESTED PANEL OPENING IS INTENDED TO GIVE THE USER THE ABILITY TO HAVE REASONABLE JACK / PANEL CLEARANCES YET MAINTAIN RELIABLE GROUNDING CAPABILITY.
2. ALL TOLERANCES NOT OTHERWISE SPECIFIED TO BE $\pm .005 [0.13]$

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND PROPERTY OF BEL STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONTENT OF BEL STEWART CONNECTOR. THE SUBJECT MATTER MAY BE PATENTED OR A PATENT MAY BE PENDING.

Bel Stewart Connector
11118 Susquehanna Trail, South
Glen Rock, Pa 17327-9199
717.234.7512

MagJack®

<http://www.stewartconnector.com>

SHEET
4 OF 4

DRAWING NO.

SI-50076-F

REV.

05