


Thin Film 0402 Size Resistor on Alumina



Product may not be to scale

FEATURES

- Wire bondable
- Small single chip size: 0.020 inches x 0.040 inches
- Resistance range: 10 Ω to 24 k Ω
- Alumina substrate
- Low stray capacitance: < 0.2 pF
- Resistor material: Nichrome
- Resistor passivation coat optional
- Solder Pads optional

The CC1 series single-value resistor chips offer a small size, low shunt capacitance and solder pad option. The CC1s nichrome resistor material offers excellent stability.

The CC1s are manufactured using Vishay Electro-Films (EFI) sophisticated thin film equipment and manufacturing technology. The CC1s are 100 % electrically tested and visually inspected to MIL-STD-883.

APPLICATIONS


Vishay EFI CC1 chip resistors provide excellent high-frequency response and are ideally suited for prototyping.

Typical application areas are:

- Amplifiers
- Oscillators
- Attenuators
- Couplers
- Filters

Recommended for hermetic environments where die is not exposed to moisture.

TEMPERATURE COEFFICIENT OF RESISTANCE, VALUES* AND TOLERANCES






Note

* Only 25 Ω to 1 k Ω are standard strip line designs for microwave applications

STANDARD ELECTRICAL SPECIFICATIONS

PARAMETER	
Noise, MIL-STD-202, Method 308	- 20 dB typ.
Moisture Resistance, MIL-STD-202, Method 106 - Hermetic applications	± 0.2 % max. $\Delta R/R$
Stability, 1000 h, + 125 °C, 40 mW	± 0.1 % max. $\Delta R/R$
Operating Temperature Range	- 55 °C to + 125 °C
Thermal Shock, MIL-STD-202, Method 107, Test Condition F	± 0.25 % max. $\Delta R/R$
High Temperature Exposure, + 150 °C, 100 h	± 0.1 % max. $\Delta R/R$
Dielectric Voltage Breakdown	400 V
Insulation Resistance	10^{12} min.
Operating Voltage	100 V max.
DC Power Rating at + 125 °C (Derated to Zero at + 150 °C)	40 mW max.
5 x Rated Power Short-Time Overload, + 25 °C, 5 s	± 0.25 % max. $\Delta R/R$



DIMENSIONS in inches

SCHEMATIC


MECHANICAL SPECIFICATIONS in inches	
PARAMETER	
Chip Size	0.020 x 0.040 ± 0.003 (0.5 mm x 1.0 mm ± 0.08 mm)
Chip Thickness	0.010 ± 0.002 (0.254 mm ± 0.03 mm)
Chip Substrate Material	99.6 % alumina, 2 microinch to 4 microinch finish
Resistor Material	Nichrome
Bonding Pad Size	0.010 x 0.012 (0.175 mm x 0.30 mm)
Number of Pads	2
Pad Material	25 kÅ minimum gold standard
Backing	None

GLOBAL PART NUMBER INFORMATION																
Global Part Number: CC1-12500KKSSNHWS																
Global Part Number Description: CC1- 1.25K 10 %, 100 ppm/°C, std trim, SnPb contacts, no back metal, class H, WS																
C	C	1	-	1	2	5	0	0	K	K	S	S	N	H	W	S
MODEL	RESISTANCE	RES. MULTIPLIER CODE	TOL. CODE (%)	TCR (ppm/°C)	TRIM STYLE	TERMINATION	BACK METAL	VISUAL CLASS	PACKAGING CODE							
CC1-	First 4 digits are significant figures of resistance	B = 0.01 A = 0.1 0 = 1 1 = 10	B = 0.1 C = 0.25 D = 0.5 F = 1.0 G = 2.0 J = 5.0 K = 10	E = ± 25 C = ± 50 K = ± 100	E = Edg S = Std U = Usr	G = Au S = SnPb A = Al T = Lead (Pb)-free (e1)	G = Au N = None	H = Class H K = Class K	WS = Waffle pack 100 min, 1 mult							

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.