

Led Signalleuchten Einbaudurchmesser 8 mm
Led Indicators Body diameter 8 mm

Trio Led, mit Außenreflektor
Trio Led, with exterior reflector

查询"19TR0A12"供应商

[illegible]

Rot blinkende / grün statische Led Signalleuchten lieferbar.

Bei Bestellung bitte an die vierte Stelle der jeweiligen Bestellnummer ein "B" einsetzen.

Red flashing / green static Led can be supplied.

When ordering, please use on the relevant partnumber a "B" for the fourth digit.

Arbeitstemperatur (T_{OP}): -55°C - +70°C
Lagertemperatur (T_{STG}): -55°C - +100°C

* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0 Schwarzchrom = 1

Beispiel: 19TR0A06 6V mit Glanzchrom
19TR1A06 6V mit Schwarzchrom

Schaltungsmöglichkeiten:

Rot, grün oder gelb. Beide Dioden ergeben gelb als Farbmischung



Led Signalleuchten mit anderen Spannungen auf Anfrage
Technische Änderungen vorbehalten

Technische Änderungen vorbehalten

Operating temperature (T_{OP}): -55°C - +70°C
Storage temperature (T_{STG}): -55°C - +100°C

* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0 Black chrome = 1

Example: 19TR0A06 6V with bright chrome
19TR1A06 6V with black chrome

Operation modes:

Red, green or yellow. Both diodes produce yellow as a mixed colour.



Led Indicators with other voltages upon request

Specification subject to change without notice.