



Led Signalleuchten Einbaudurchmesser 6 mm
Led Indicators Body diameter 6 mm

[查询"19020256"供应商](#)

Zweifarbige, mit Außenreflektor
Duo Led, with exterior reflector

Bestell-Nr.	Farbe	V _{OP} +10%	I _{OP max.}	V _F	I _{V typ} (mcd)	I _{F max.}	Abb.	Abmessungen, siehe Zeichnungsnr.	
Part No.	Colour	(V)	(mA)	(V)	*I _F = 20mA	(mA)	Illu.	Dimensions, see Drawing No.	
1902*004	Super red/ Green			2,0/2,2 2,2/2,8	*10/13	30	A		19020-A A
1902*005	Super red/ Yellow			2,0/2,2 2,2/2,8	*10/10	30	A		
1902*006	Green/ Yellow			2,0/2,2 2,2/2,8	*13/10	30	A		
1902*054	Super red/ Green			2,0/2,2 2,2/2,8	*10/13	30	B		
1902*055	Super red/ Yellow			2,0/2,2 2,2/2,8	*10/10	30	B		
1902*056	Green/ Yellow			2,0/2,2 2,2/2,8	*13/10	30	B		
1902*154	Super red/ Green	6	30		15/18		B		
1902*155	Super red/ Yellow	6	30		15/15		B		
1902*156	Green/ Yellow	6	30		18/15		B		
1902*254	Super red/ Green	12	30		15/18		B		19020-B B
1902*255	Super red/ Yellow	12	30		15/15		B		
1902*256	Green/ Yellow	12	30		18/15		B		
1902*354	Super red/ Green	24	18		9/11		B		
1902*355	Super red/ Yellow	24	18		9/9		B		
1902*356	Green/ Yellow	24	18		11/9		B		

Arbeitstemperatur (T_{OP}): -55°C - +70°C
 Lagertemperatur (T_{STG}): -55°C - +100°C

* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0 Schwarzchrom = 1

Beispiel: 19020004 super rot / grün mit Glanzchrom
 19021004 super rot / grün mit Schwarzchrom

Operating temperature (T_{OP}): -55°C - +70°C
 Storage temperature (T_{STG}): -55°C - +100°C

* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0 Black chrome = 1

Example: 19020004 super red / green with bright chrome
 19021004 super red / green with black chrome

Led Signalleuchten mit anderen Spannungen auf Anfrage

Technische Änderungen vorbehalten

Led Indicators with other voltages upon request

Specification subject to change without notice

