IEC plug connector l, rewirable, straight 查询"0922" 供应商











Description

- Rewireable plug: Screw-on
- Appliance Inlet, Pin temperature 70 °C, Protection class I
- Cable

Approvals

- UL License Number: E96454 - CSA License Number: 205419

Characteristics

- For use in equipment acc. IEC 60950/60601

References

General Product Information

Weblinks

Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check


Technical Data

| Ratings IEC | 16 A / 250 VAC; 50 Hz |
|---------------------------|---|
| Ratings UL/CSA | 20 A / 250 VAC; 60 Hz |
| Dielectric Strength | > 2 kVAC between L-N |
| | > 2 kVAC between L/N-PE |
| | (1 min/50 Hz) |
| Allowable Operation Temp. | -25 °C to 70 °C |
| Degree of Protection | from front side IP 40 acc. to IEC 60529 |
| Protection Class | Suitable for appliances with protection |
| | class I acc. to IEC 61140 |
| <u>Terminal</u> | Cable |
| Material: Housing | Thermoplastic, black, UL 94V-0 |
| | |

| Appliance-Inlet/-Outlet | I acc. to IEC/EN 60320-2-2, |
|-------------------------|---|
| | UL 498, CSA C22.2 no. 42 (for cold |
| | conditions) pin-temperature 70 °C, 16A, |
| | Protection class I |

Dimensions

-138 mm Length !



Variants

Distributor-Stock-Check | SCHURTER-Stock-Check | e-Store

| Color | Max. cable diameter | Max. wire size | Order Number |
|-------|---------------------|----------------|--------------|
| black | 12.0 mm | 3 x 12 AWG | 4300.0922 |

Packaging unit 100 Pcs

www.schurter.com/pg07b

Mating wille w Can 技術 商

Category / Description



Appliance Outlet

| IEC appliance outlet J, screw-on mounting, front side, solder/quick connect terminal | 0723 |
|--|------|
| IEC appliance outlet J, snap-in/screw-on mounting, front side, solder/quick connect terminal | 4797 |
| IEC appliance outlet J, snap-in mounting, front side, quick connect terminals | 5013 |
| IEC appliance outlet J, screw-on mounting, front side, quick connect terminals | 5016 |
| IEC appliance outlet J, screw-on mounting, front side, quick connect terminals | 5017 |
| IEC appliance outlet J, screw-on mounting, front side, quick connect terminals | 5216 |

Connector



| IEC connector C19, rewirable, straight | 0104 |
|--|------|
| IEC connector C19, rewirable, angled | 1651 |
| IEC connector C19, rewirable, straight | 1652 |
| IEC connector C19, rewirable, angled | 4790 |
| IEC connector C19, rewirable, straight | 4795 |



Rewireable Connector for Cable, straight entry

| IEC cord connector C19, rewirable, straight | 0921 |
|---|------|
| | |